

SCAN CODE TO
WATCH VIDEO



Learn more about the
production of 182mm
Mono PV Solar Module

SKT390~415M10

390~415 Watt

182mm 108Cells All Black Dul-glass/Transparent Bifacial PV Module



MBB PERC
Half Cut Cell



Excellent Low-light
Performance



100% Inspection
Guarantee Reliability



Anti PID




Strengthened
Mechanical Load




High Density
Packaging





All Dimensions in mm
The above drawing is a graphical representation of the product.
For engineering quality drawings please contact SUNKET.



Electrical Characteristics (STC/NOCT)

Module Type	SKT390M10		SKT395M10		SKT400M10		SKT405M10		SKT410M10		SKT415M10	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power- Pmax(W)	390	294	395	298	400	302	405	306	410	310	415	314
Open Circuit Voltage - Voc(V)	36.85	34.62	36.98	34.75	37.07	34.88	37.23	35.12	37.32	35.23	37.45	35.37
Short- Circuit Current - Isc(A)	13.61	10.89	13.70	10.96	13.79	11.03	13.87	11.10	13.95	11.16	14.02	11.22
Voltage at Pmax -Vmp(V)	30.64	28.87	30.84	29.08	31.01	29.26	31.21	29.47	31.45	29.72	31.61	29.89
Current at Pmax - Imp(A)	12.73	10.18	12.81	10.25	12.90	10.32	12.98	10.38	13.04	10.43	13.13	10.50
Module Efficiency -ηm(%)	20.0	/	20.2	/	20.5	/	20.8	/	21.0	/	21.3	/
Power Tolerance(W)	(0, +4.99W)											
Maximum System Voltage(V)	1500Vdc (IEC / UL)											
Maximum Series Fuse Rating (A)	25A											

STC : Irradiance 1000W/m², Cell Temperature 25℃, Air Mass 1.5

NOCT : Irradiance 800W/m², Ambient Temperature 20℃, Air Mass 1.5, Wind Speed 1m/s

Mechanical Specifications

External Dimensions	1724x1134x30mm
Weight	20.5g
Solar Cells	Mono crystalline 182mm (2x54pcs)
Front Glass	AR Coated 2.0+2.0 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	1.2m
Connector	MC4 EVO2
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

Pmax Temperature Coefficient	-0.350%/℃
Voc Temperature Coefficient	-0.275%/℃
Isc Temperature Coefficient	+0.045%/℃
Operating Temperature	-40~+85℃
Nominal Operating Cell Temperature(NOCT)	45±2℃

Packing Configuration

	1724x1134x30mm	
Container	20'GP	40'HQ
Pieces per Pallet	36	36
Pallets per Container	6	26
Pieces per Container	216	936

Current-Voltage & Power-Voltage Curves (SKT415M10)

